

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number
WO 2005/019627 A1

(51) International Patent Classification⁷: **F02D 13/02**,
21/08, 41/26, 43/04, F02B 1/12

[SE/SE]; Vasagatan 9, Igh 413, S-172 67 Sundbyberg (SE).
AGRELL, Fredrik [SE/SE]; Bettnavägen 46, S-125 43
Älvsjö (SE).

(21) International Application Number:
PCT/SE2004/001212

(74) Agent: **WALDEBÄCK, Hans**; Scania CV AB, Patents,
S-151 87 Södertälje (SE).

(22) International Filing Date: 19 August 2004 (19.08.2004)

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0302247-2 20 August 2003 (20.08.2003) SE

(71) Applicant (*for all designated States except US*): **SCANIA
CV AB (publ)** [SE/SE]; S-151 87 Södertälje (SE).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **LINDERYD, Johan**

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: ARRANGEMENT AND METHOD FOR CONTROLLING A COMBUSTION ENGINE



(57) Abstract: The present invention relates to an arrangement and a method for controlling a combustion engine (1), e.g. of the type called HCCI engine. The arrangement comprises a control unit (19) adapted to controlling the self-ignition of the fuel mixture towards an optimum crankshaft angle (cad_{opt}) within a load range (L_{tot}). Said load range (L_{tot}) can be divided into at least two subranges (L_{II} , L_{III}) and the control unit (19) is adapted to controlling the self-ignition of the fuel mixture towards an optimum crankshaft angle (cad_{opt}) within one of said subranges (L_{II}) by means of a strategy (II) which entails the effective compression ratio (c) in the cylinder (2) being varied, and within the second subrange (L_{III}) by means of another strategy (III) which entails a variable amount of cooled exhaust gases (ceg) being led to the combustion chamber (3) so that it becomes possible also in the second subrange (L_{III}) to control the self-ignition of the fuel mixture towards an optimum crankshaft angle (cad_{opt}) by variation of the effective compression ratio (c) in the cylinder (2) without it falling below a lowest acceptable value (c_{min}).



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*